

**COMPARISON
OF
PDA CH. 82
AND USDOL 29 CFR 1910.142(OSHA) AND 20 CFR 654 (ETA)
HOUSING/CAMP STANDARDS**

Note: Bolded descriptions are the strictest regulation. Where both were equal, PDA was highlighted.

AREA OF CONCERN	PDA, CH 82	UDDOL, OSHA: BUILT AFTER 4/80	USDOL, ETA: BUILT BEFORE 4/80
PERMITTING LICENSING APPLICATION	<p>Yes.</p> <p>Pre-permit inspections (announced) and post-permit inspections (unannounced). Renewal applications made annually 45 days prior to occupancy or permit expiration. Permits valid for 1 year. Posting of permit required. Permits may be revoked or suspended at any time for violation of this chapter or the act. Occupancy of camp may not occur without a valid permit. New camp application must be made 60 days prior to occupancy. Separate permits are required for each camp. Plans and specifications must be submitted to the Department for any construction, remodel, alteration, or new camp.</p>	<p>Migrant & Seasonal Agricultural Worker Protection Act 500.130 – 500.135 defines.</p> <p>Inspections occur randomly. Accepts PA permit</p>	<p>Migrant & Seasonal Agricultural Worker Protection Act 500.130 – 500.135 defines.</p> <p>Inspections occur randomly. Accepts PA permit</p>
OCCUPANCY			
How many?	<p>Determined by square ft of useable floor space in sleeping rooms and habitable rooms (areas where ceiling height is > 5’ and > ½ of the area has a ceiling height of 7’) 82.5. a and e</p>	<p>Determined by square ft of useable floor space in sleeping rooms and habitable rooms</p> <p>7 ft ceiling provided. 1910.142 (b) (2)</p>	<p>Determined by square ft of useable floor space in sleeping rooms and habitable rooms: areas where ceiling height is > 5’ and > ½ of the area has a ceiling height of 7’ 654.407(g)</p>

**COMPARISON
OF
PDA CH. 82
AND USDOL 29 CFR 1910.142(OSHA) AND 20 CFR 654 (ETA)
HOUSING/CAMP STANDARDS**

Note: Bolded descriptions are the strictest regulation. Where both were equal, PDA was highlighted.

Occupancy cont.			
Dorm/other sleeping quarters	Shared by unrelated SFW's = 50 sq ft/adult, 25sq ft /occupant under age 14 82.5a (1)	>50 sq ft/person 1910.142 (b)(2)	>50 sq ft/person for single beds and > 40 sq ft /person for double bunks in dorm situations 654.407 9 (c)(1) and (c)(2)
Living units: 1+ rooms Where workers live, sleep and eat.	100 sq ft of floor space/adult 50 sq ft /occupant under 14 82.5a (2)	>100 sq ft/person 1910.142 (b)(9)	>60 sq ft/person 654.407 (c)(3)
Other requirements	Family with children 6 or older-1 rigid partition for privacy in sleeping quarters. 82.5b.	None	Separate or partitioned sleeping areas for parents where children are >age 6. 654.407 (d) Separate sleeping for each family. 654.407 (e)
Sleeping Rooms contents	Provided with bed, mattress & cover, pillow & cover, sheets, and blankets. Single-family occupancy units-- family can provide linens. Must have linens for occupancy. 82.5b.(a)	Beds, cots, bunks provided 1910.142 (b)(3)	Provided; beds, cots, bunks 654.416 (a) Clean mattress 654.416 (a) Clean and sanitary linens provided 654.416 (b)
Spacing of beds	Bed, bunk, cot = 12 inches from floor/ 36'' apart all sides. Double bunks = 48''apart all sides/27'' between upper & lower. Triple bunk prohibited. Double beds = single family sleeping rooms only. 82.5b. (a)1 thru 5	Beds, cots, bunks >3' apart and 12'' off floor. Triple bunks prohibited. Double bunk beds spaced >48'' both laterally and end to end . clear space between lower and upper bunk = 27''. 1910.142 (b)(3)	No specific mention

**COMPARISON
OF
PDA CH. 82
AND USDOL 29 CFR 1910.142(OSHA) AND 20 CFR 654 (ETA)
HOUSING/CAMP STANDARDS**

Note: Bolded descriptions are the strictest regulation. Where both were equal, PDA was highlighted.

Occupancy cont.			
Storage in sleeping rooms	In the sleeping room area. Wall or footlocker, 3 ft of rod and shelving, dresser or equivalent/occupant. 82.5b	Suitable storage, facilities, wall lockers provided. 1910.142 (b)(3)	Adequate facilities for hanging and storing personal effects provided 654.401 (f)
Maintenance of sleeping rooms	Aired, in sanitary condition at all times. Bedding and linens cleaned frequently. 82.6 (a) and (b) Single family units responsible for own frequency on cleaning.	No specific mention	Maintained in sanitary condition 654.407(a)
SITE			
Drainage	Adequately drained 82.4	Adequately drained 1910.142 (a)(1)	Adequately drained 654.404 (a)
Location	Not within 500 ft of swamp, pools, sink holes or other surface collection of water UNLESS the water is subject to mosquito control measures. Nor along, across or projecting into floodways or flood channel. 82.4. a and b	May not be subject to periodic flooding nor located within 200 ft of swamp, pools, sink holes, or other surface collections of water UNLESS the water is subject to mosquito control measures. Drained so not to cause a danger to the domestic or public water supply 1910.142 (a)(1)	Away from conditions that could create offensive odors, flies, noise, traffic, or similar hazards. 654.404 (b) Provided with reasonable recreational space relevant to camp size 654.404 (d)
Grading /exterior maintenance	Site graded, ditched, or rendered free from depressions. 82.4.a	Site graded, ditched, or rendered free from depressions. 1910.142 (a)(1)	Free from debris, poisonous plants, uncontrolled weeds or brush 654.404 (c)
Location near farm animals	At least 500 ft from area with livestock (with some exceptions). Animal waste produced for ag. purposes must be managed to not be a nuisance or fly breeding medium. 82.4. c and f	At least 500 ft from area with livestock. 1910.142(a)(2)	No comments regarding

**COMPARISON
OF
PDA CH. 82
AND USDOL 29 CFR 1910.142(OSHA) AND 20 CFR 654 (ETA)
HOUSING/CAMP STANDARDS**

Note: Bolded descriptions are the strictest regulation. Where both were equal, PDA was highlighted.

Site cont.			
Grounds	Clean and sanitary, free from refuse, debris, waste paper, garbage, noxious plants, uncontrolled weeds, abandoned autos, or other refuse. Removal of all refuse when camp is closed and privy locked. 82.4.d	Clean and sanitary, free from rubbish, debris, waste paper, garbage, or other refuse. Removal of all refuse when camp is closed and privy locked. 1910.142(a)(3)	Free from debris, poisonous plants, uncontrolled weeds or brush 654.404(c)
HOUSING/SHELTER			
Types allowed	<ol style="list-style-type: none"> 1) Bldg for habitation by humans only. 2) Fully partitioned rooms in bldgs. used for other purposes except livestock shelter. 3) Approved mobil homes. 4) Separate dormitory or sleeping room shared by unrelated SFW shall be separate for each sex. 82.5. b,c,d	No specific mention	Separate sleeping for each sex in non-family groups. 654.407 (e)
Construction/repair: Walls	Sound condition and good repair. Protected from weathering <ol style="list-style-type: none"> 1) Foundation- if used as a common wall 50% above ground level in and out in habitable rooms. 2) Exterior wall of wood protected from weathering 3) Exterior walls of masonry moisture barrier in interior 82.5. b and c	Provide protection against the elements. Banking of materials is allowed on outside walls. 1910.142(b)	Structurally sound, in good repair, maintained in sanitary condition, protection against the elements. 654.477(a)

**COMPARISON
OF
PDA CH. 82
AND USDOL 29 CFR 1910.142(OSHA) AND 20 CFR 654 (ETA)
HOUSING/CAMP STANDARDS**

Note: Bolded descriptions are the strictest regulation. Where both were equal, PDA was highlighted.

Housing/structure cont.			
Construction/repair: Floors	Sound and sanitary condition and in good repair. Smooth, tight and easily cleanable. 1st story wood – 18 inches above ground level shower/laundry—impervious to water, floor drains provided, floor/wall juncture coved. 82.5.b	Shall be constructed of wood, asphalt, or concrete. Wooden floors= smooth and tight construction and in good repair. Wooden floors elevated 1 ft above the ground level—so to prevent dampness and air circulation. Provided to protect against the elements. 1910.142 (b)(4)	Smooth, rigid, cleanable. 654.407 (b)
Construction/repair: Windows	In habitable rooms--Weather tight, operable, in good repair and: 1) size = 10% of floor area 2) 45% of window area openable (unless otherwise ventilated). 3) Fitted screens with 16'' mesh during insect season 82.5.f	In all living quarters —total window area > 1/10 th of the floor area. ½ of window openable for ventilation. Screened with 16'' mesh at all times. In good repair. 1910.142 (b)(7), (8), and (1)	In all living quarters—total window area > 1/10 th of the floor area. 654.407 (h) Total openable window space > 45% of the minimum window area required, except where adequate ventilation is provided. 654.407(h) Screened with 16'' mesh. 654.408(a)
Construction/repair: Doors	Exterior doors weather tight, sound condition. If for ventilation fitted with 16 mesh screen door with self-closing device. 82.5.g	Effectively screened with 16'' mesh and with self-closing device at all times. 1910.142 (b) (8)	Screened with 16'' mesh. 654.408(a) Doors screened at all times and with self-closing devices. Tight fitting and in good repair. 654.408(b)
Heat	Space heating equipment: safely and adequately heating all habitable rooms to 68°f from September 15 thru May 15. Unvented or unventable heaters with a flame are prohibited. 82.5.h and i	Adequate heating equipment provided if camp is used during the cold weather. Equipment installed via state and local Laws. 1910.142(b)(11)	Provided if temp falls below 68°f. Installed properly and in good repair so temp is maintained at 68° f or above.654.409 (a) Heat sources with combustible fuel vented. 654.409(b). No portable heater other than electric. 654.409 (b)

**COMPARISON
OF
PDA CH. 82
AND USDOL 29 CFR 1910.142(OSHA) AND 20 CFR 654 (ETA)
HOUSING/CAMP STANDARDS**

Note: Bolded descriptions are the strictest regulation. Where both were equal, PDA was highlighted.

<i>WATER</i>			
Availability and supplied	Shall be provided with an approved water supply. 82.7.a	Shall be distributed so that no shelter is more than 100 feet from a yard hydrant if water is not piped to the shelter. 1910.142 (c)(3) Shall have water provided for drinking, cooking, bathing, and laundry purposes. 1910.142 (c)(1). Adequate heating equipment provided during cold months.1910.142 (f)(3)	Adequate and convenient water supply provided. 654.405 (a)
Heating equipment	Supplied and maintained. Unvented or unventable heaters with a flame are prohibited.	Installed and operated according to State and Local Codes. 1910.142 (b)(11)	Heating pipes of fireproof materials 654.409(c) Vents with metal collars 654.409 (c)
Hot water supplied	Hot water (120°f) shall be provided to kitchens, lavatories, showers, tubs, and laundry. Hot and cold water supplied to the kitchen and laundry facilities. 82.7.i and 82.11.d	Adequate supply of hot and cold water available for bathing and laundry. 1910.142(b)(11)	Sinks with hot and cold water provided 654.413(b)(5)
Supply approved	Approved water system (Pa Safe Drinking Water Act). Non-public water systems testing for total Coliform and nitrates/nitrites annually and supplied at the initial inspection and passed. Unapproved systems made inaccessible to camp residents. 82.7. a thru f	Approved by the appropriate Health authority. 1910.142 (c)(1)	Must meet State health Department Standards. 654.405 (a)

**COMPARISON
OF
PDA CH. 82
AND USDOL 29 CFR 1910.142(OSHA) AND 20 CFR 654 (ETA)
HOUSING/CAMP STANDARDS**

Note: Bolded descriptions are the strictest regulation. Where both were equal, PDA was highlighted.

Water cont.			
Supply demands	Delivers 50 gal/person/day at peak time at a peak rate of 2 ½ times the average hourly demand and capable of providing a max. daily and hourly demands. 82.7.g	Adequate if delivers 35 gal/person/day at peak rate of 2 ½ x the average hourly demand. 1910.142 (c)(1) and (2)	Adequate water supply. Must meet State Health Authority Standards 654.405(a)
Supply pressure	Normal operating pressure (fixtures not less than 8lbs/sq ft and direct flush valves not less than 15 lbs/sq ft) supplied to all fixtures for simultaneous operation. 82.7.h	Normal operating pressure (fixtures not less than 8lbs/sq ft and direct flush valves not less than 15 lbs/sq ft) supplied to all fixtures for simultaneous operation.1910.142(c)(3)	Water under pressure for bathing and hand washing. 654.412 (a)
Drinking fountains	1 or more /100 or a fraction thereof (excluded SFHU). Impervious materials. Angle jet nozzle with non-oxidizing guard above the rim of the bowl. Pressure regulating valve. Kept sanitary. If inadequate, single service cup must be provided (waste receptacle).82.7.j	Where water is available under pressure, 1+ fountains shall be provided/100 occupants or a fraction thereof. Construction must meet ANSI Standard Specifications (Z4.2-1942). Common drinking cups prohibited. 1910.142 (c)(4)	Not applicable
PLUMBING			
Installed/maintained	To safely carry adequate quantities of water to required locations and properly convey sewage and liquid wastes from the location to the sewage disposal system. In accordance with 1978 edition of Basic Plumbing Code (BOCA) or any edition in effect at time of construction. Prevent contamination of water supply. Prevent unsanitary conditions or nuisance. 82.8.a and b	General Provisions of OSHA	Maintained to allow for disposal of sewage. 654.406 (a)

**COMPARISON
OF
PDA CH. 82
AND USDOL 29 CFR 1910.142(OSHA) AND 20 CFR 654 (ETA)
HOUSING/CAMP STANDARDS**

Note: Bolded descriptions are the strictest regulation. Where both were equal, PDA was highlighted.

<i>TOILET FACILITIES</i>			
Numbers	Adequate for the capacity of the camp. Separate for sexes. 1 –5 occupants of 1 sex = 1 6 – 30 occupants of 1 sex = 2 31 – 45 occupants of 1 sex= 3 46 – 60 occupants of 1 sex= 4 If < 6 occupants irrespective of sex = 1, if locked from the inside and in a single occupancy toilet facility. SFHU's and apartments = each with its own 82.9.a,b,e,	Adequate for the capacity of the camp. Separate for sexes in multifamily/barracks type units. 1 unit/ 15 persons. With a minimum of 2 units for any shared facility. 1910.142 (d)(3) and (5)	1 unit/15 occupants 654.411(b) separate for sexes
Urinals	2 linear ft or 1-unit/18 men. # of water closets needed reduced by 1/3 by installing urinals. 82.9.c	2 linear ft or 1 unit/ 25 men Adequate water flush, drain freely and exclude pests.1910.142 (d)(6)	Non-absorbent material. Substituted in a ratio of 1 urinal or 24'' for one toilet up to 1/3 654.411 (c)
Structure	In central toilets, water closets separated by partitions. If facilities for each sex are in the same bldg then separate by solid walls or partitions extending from floor to ceiling/roof. Floor around urinals (>15'' from outer edge) = impervious materials. Sanitary design/cleanable. A window not less than 6 sq ft in area opening directly to the outside or satisfactorily ventilated (properly screened). Privy bldg vented by opening at least 2 sq ft. Outside openings screened with 16'' mesh. 20-foot candles of light at any time. Approaches to may not be obstructed. 82.9 a,c,d,e,g,i	If facilities for each sex are in the same bldg then separate by solid walls or partitions extending from floor to ceiling/roof. 1910.142(d)(4) Floor around urinals (>15'' from outer edge) = impervious materials. Windows not less than 6 sq ft in areas opening directly to the outside or otherwise vented. Outside openings screened with 16'' mesh. 1910.142(d)(2) Lighted naturally or artificially by safe lighting all times. 1910.142 (d)(8)	Men & women facilities separated by solid walls floor to ceiling. 654.411 (d) Fly tight structure 654.411 (h) Well lighted, ventilated, sanitary 654.411 (f) Constructed to prevent nuisance/health hazard 654 411 (a)

**COMPARISON
OF
PDA CH. 82
AND USDOL 29 CFR 1910.142(OSHA) AND 20 CFR 654 (ETA)
HOUSING/CAMP STANDARDS**

Note: **Bolded descriptions are the strictest regulation.** Where both were equal, PDA was highlighted.

Toilet facilities- cont.			
Located	<p>No fixture, water closet, urinal, chemical toilet shall located in a room other than for toilet purposes. Within 200 ft of sleeping room door. Not closer than 100 ft to a sleeping room, dining room, lunch or kitchen room.</p> <p>82.9.f and h</p>	<p>So as to be accessible without any individual passing through any sleeping room. 1910.142(c)(4) Pits/vaults keep out rodents and flies. 1910.142 (d)(6) Installed after 8/31/71: located in toilet room 1910.142(d)(7) Within 200 ft of sleeping room door. Not closer than 100 ft to a sleeping room, dining room, lunch or kitchen room. 1910.142(d)(3)</p>	<p><200' from living units 654.411(g) >50' from living/cooking areas 654.411 (h) Located to prevent nuisance/health hazard 654.411 (a)</p>
Supplied	<p>Adequate supply of toilet paper in each privy, water closet or chemical toilet compartment. Kept in clean and sanitary condition. Must be signed in English and native language of occupant or marked with understandable picture or symbol.</p> <p>82.9.j and k</p>	<p>Adequate supply of toilet paper in each 1910.142(d)(9) Kept sanitary and cleaned daily.1910.142(d)(10)</p>	<p>Toilet tissue supplied (common use facilities) 654.411 (e) Marked "men" & "women" in native language 654.411 (d)</p>
LAUNDRY/HAND WASHING/ BATHING			
Numbers	<p>1 hand wash basin/6 persons 1 showerhead/10 persons 1 mechanical washing machine or double laundry tray or 2 tubs /30 persons OR transportation 1x weekly OR commercial linen service 1 slop sink/camp 1 tub/6 occupants as an alternative to showers. 82.11.a</p>	<p>1 hand wash basin/family or 6/persons in shared facility 1 showerhead/10 persons 1 laundry tub or tray/ 30 persons 1 slop sink/building</p> <p>1910.142 (f)(2) (i) and (ii) and (iii) and (iv)</p>	<p>Showerheads = 1/15 654.412(b) Wash basins = 1/15 654.412 (c) Laundry tub/trays = 1/25 OR Washing machine = 1/50 654.412 (d) Separate shower facilities for sexes (except family units) 654.412 (b)</p>

**COMPARISON
OF
PDA CH. 82
AND USDOL 29 CFR 1910.142(OSHA) AND 20 CFR 654 (ETA)
HOUSING/CAMP STANDARDS**

Note: Bolded descriptions are the strictest regulation. Where both were equal, PDA was highlighted.

Floors	Non-slippery finish, easily cleanable surface, impervious to moisture, floor drains provided, floor/wall coving installed. Shower room walls/floor smooth and impervious to height of splash. 82.11.b and c	Smooth finish, not slippery, impervious to moisture, drains provided, curbing and floors coved, walls/shower partitions smooth and impervious to height of splash. 1910.142 (f)(2)	Non absorbent, non skid, with proper drains 654.412 (b)
Other	Adequate hot and cold running water with normal operating pressure. Facilities to dry clothing provided. Bathing tubs—adequate hot and cold water under pressure. Common towels prohibited Dry dressing area provided in or adjacent to shower facility. 82.11.d,e,f,g,i,j	-Adequate hot and cold running water provided. -Facilities for heating water provided -Service bldgs provided with heat (70°F) -Facilities for drying clothing provided -Kept clean 1910.142 (f)(3) and (4) and (5) and (6)	Bathing and hand washing provided, hot and cold water under pressure provided in bathing, laundry and hand washing areas, maintained clean and sanitary, located within 200' of living unit, 654.412 (a) (b) Shower area with >9sq ft of floor space/worker 654.412(b)
<i>SEWAGE</i>	Approved by the Department or the municipal Sewage Enforcement Officer (Ch 71,73, and 243 and The Clean Streams Act). 82.10	In camps where public sewers are available, all sewer lines and floor drains from the bldg. shall be connected thereto. 1910.142 (e)	Facilities for effective disposal provided, maintained, connection to public sewer where available. 654.406 (a) (b) Portable privies provided where public sewer or septic not available 654.406 (c)
<i>LIGHTING/ELECTRICAL</i>			
Installed/maintained	Comply with Ch 82 and 1978 National Electrical Code (NFPA) except built prior to 1/3/81: comply with code in effect at time of construction. Proof of electrical certification submitted in duplicate to Dept. 82.12.a and b	General provisions of OSHA, BOCA, NEC, state and local codes	Electricity provided 654.410 (a) Wiring and lighting fixtures in safe condition 654.410(d) General provisions of OSHA, BOCA, NEC, State and local codes

**COMPARISON
OF
PDA CH. 82
AND USDOL 29 CFR 1910.142(OSHA) AND 20 CFR 654 (ETA)
HOUSING/CAMP STANDARDS**

Note: Bolded descriptions are the strictest regulation. Where both were equal, PDA was highlighted.

Lighting cont.			
<p>Levels (Measured minimum 30'' from the floor)</p>	<p>Area</p>	<p>Foot candles</p>	<p>Light levels in toilet and storage areas = 20 foot candles measured 30'' from floor.</p> <p>Other rooms = 30 foot candles 30'' from the floor</p> <p>Where service is available: Habitable Room = 1 ceiling type light fixture Laundry rm, toilet rm, rooms where people congregate = 1 ceiling or wall-type fixture.</p> <p>1910.142 (g)</p>
	<p>Food storage Central kitchen 35(work)/20(general) Communal kitchen 30(work)/20(general) Private kitchen 30(work)/20(general) Dining Rm (for cleaning) Laundry Rm Halls/stairways Habitable rooms Living quarters Private sleeping Dorm sleeping Toilet/bathing: Shared and private Chemical toilets</p>	<p>10 10 20 10 20 20 20 20 20 20 20 20 20 20 20 20 20 20</p>	<p>Adequate ceiling/wall type fixtures in all rooms. 654.410 (b) Adequate lighting for pathways and yard 654.410 (c)</p>
<p>Outlets</p>	<p>Room</p>	<p>Outlet number</p>	<p>1 separate floor or wall-type convenience outlet in each habitable room. 1910.142 (g)</p>
	<p>82.12.d (not on floor surface) Food storage Existing central, communal, private kitchens New kitchen Laundry Halls/stairways Habitable rms/living quarters Sleeping private Sleeping, Dorm Toilet/bathing private Toilet shared</p>	<p> 0 2(1 = 20 amp) 2, 20 amp 1 0 1 1/person 1/5 persons 1 1 / 2 sinks</p>	<p>Electrical outlets provided in each room. 654.410 (b)</p>

**COMPARISON
OF
PDA CH. 82
AND USDOL 29 CFR 1910.142(OSHA) AND 20 CFR 654 (ETA)
HOUSING/CAMP STANDARDS**

Note: Bolded descriptions are the strictest regulation. Where both were equal, PDA was highlighted.

<i>REFUSE</i>			
Type	Those containing food waste: leak proof, nonabsorbent, rust/corrosion resistant, tight fitting lids, kept clean. Other refuse: sufficient size; must prevent arthropod/rodent/other nuisances. 82.13. a,b	Fly-tight, rodent-tight, impervious, cleanable or single service containers, approved by the local health authority, kept clean. 1910.142 (h) (1) and (2)	Fly tight 20 gallon container provided adjacent to housing unit = 1/15persons 654.414 (a)
Located	Adjacent and convenient to kitchens, dining rooms, living quarters and toilet rooms. 82.13.c	Within 100 ft of each shelter and on wood, metal, or concrete stand. 1910.142 (h)(1)	Fly tight 20 gallon container provided adjacent to housing unit = 1/15persons 654.414 (a)
Numbers	Sufficient in number. 82.13.b	1/family shelter 1910.142 (h)(1)	1/15persons 654.414 (a)
Disposal	1x/week emptied or whenever full. Containers kept clean after removal. Shall conform to July 7, 1980 Solid Waste Management Act and 25 Pa. Code Part I, Subpart D, Article VIII. 82.13.d,e,f	Emptied when full but not less the 2x/week. 1910.142 (h)(3)	Collected 2 x /week or more often 654.414 (b)
<i>RODENT/INSECT CONTROL</i>			
Prevention	Effective control measures and environmental change approved by the Dept. to control infestations and harborage of animals and insects. 82.15.a	Effective measures shall be taken to prevent infestation by and harborage of animal or insect vectors or pests. 1910.142(j)	Free from rodent, insect, vermin 654.415
Other	Agricultural pesticides and toxic chemicals may not be stored in housing areas. 82.15.(c)	Poisonous/toxic materials not stored with food or in food prep areas. 1910.142 (i)	Pesticides and other chemicals not stored in housing unit 654.417(i)

**COMPARISON
OF
PDA CH. 82
AND USDOL 29 CFR 1910.142(OSHA) AND 20 CFR 654 (ETA)
HOUSING/CAMP STANDARDS**

Note: Bolded descriptions are the strictest regulation. Where both were equal, PDA was highlighted.

<i>FOOD SERVICE/KITCHENS</i>			
Location	Private Kitchens: space separated but not necessarily partitioned. Communal Kitchens: in a room or building separate from the sleeping areas 82.14.a,b	Separate from the sleeping quarters of any workers or their families. No direct opening from living or sleeping quarters into kitchen or dining halls. 1910.142 (i)(2)	In family units cooking and eating equipment provided 654.413 (a) Central mess kitchens separate form sleeping quarters 654.413 (d)
Supplied Private and communal kitchens	-Stove/hot plate with min. 2 burners (2 burners/10 persons or 2 families) - Food storage shelves - Counter - Mechanical refrigeration to maintain 45°f or below and freezer accommodations. - Table and chairs adequate for capacity of camp - Adequate sinks with hot/cold running water under normal pressure - Lighting and ventilation 82.14.a,b	No specific mention	Family units/common facilities for families: cook stove with min of 2 burners (1 stove/10 people) ; shelves and counter space; mechanical refrigeration (<45 f); tables and chairs provided to accommodate capacity; provided with adequate light and ventilation. 654.413 (a) (b) In common facilities, sinks with hot and cold water under pressure. 654.413 (b)(5)

**COMPARISON
OF
PDA CH. 82
AND USDOL 29 CFR 1910.142(OSHA) AND 20 CFR 654 (ETA)
HOUSING/CAMP STANDARDS**

Note: Bolded descriptions are the strictest regulation. Where both were equal, PDA was highlighted.

Food service cont.			
Sanitation in food service kitchens	Physical facilities, equipment and operation shall comply with Ch. 78, relating to food establishments , in central kitchens. 82.14.c,d	In all camps where dining or multiple family feeding operations are permitted or provided, the food handling facility shall comply with the requirement of the "Food Service Sanitation Ordinance and Code," Part V of the "Food Service Sanitation Manual," U.S. public health Service Publication 934 (1965). 1910.142(i)(1) No person with any communicable disease shall be employed or permitted to work in the preparation, cooking, serving, or handling of food, foodstuffs, or materials used therein, in any dining room or kitchen used by persons living in a camp. 1910.142(i)(3) Free from vermin, flies, rodents. No spoiled food. Equipment and utensils clean. Kitchen clean. 1910.142(i)	Walls of nonabsorbent, cleanable materials. 654.413 (d)
Fire safety in kitchens	Wall surfaces adjacent to cooking areas shall be fire-resistant. 82.14.d	General provisions of OSHA	General provisions of OSHA, state and local fire codes. 654.417 (a) Wall surfaces adjacent to cooking areas = fire resistant materials. 654.413 (d)
FIRST AID			
How many?	1 kit/50 persons or fraction thereof. 82.16.a	Adequate first aid facilities approved by a health authority shall be maintained and made available in every camp. 1910.142(k)(1)	Provided 654.417 (g)

**COMPARISON
OF
PDA CH. 82
AND USDOL 29 CFR 1910.142(OSHA) AND 20 CFR 654 (ETA)
HOUSING/CAMP STANDARDS**

Note: Bolded descriptions are the strictest regulation. Where both were equal, PDA was highlighted.

First aid cont.			
Contents	Shall include: 50 adhesive compress, 10 4x4 gauze pads, 20 3x3 gauze pads, 10 2x2 gauze pads, 2 gauze roller bandage, 1 roll adhesive tape (1" and 1/2"), 50 cotton balls, 50 cotton swabs, 12 aromatic ammonia inhalants, 1 8oz ethyl or isopropyl alcohol, 1 8oz benzalkonium chloride, 1 scissors, 1 tweezers. 82.16.a	No specific mention	No specific mention
Responsibility	1 designated person trained to administer first aid shall be in charge of the kit and be accessible at all times. 82.16.b	1 person trained to administer first aid and shall be in charge of the kit and readily accessible at all times. 1910.142 (k)(2)	No specific mention
COMMUNICABLE DISEASE REPORTING	See Ch. 78 for communal kitchens operations	Camp superintendent shall report to the Health Authority if camp individual is know to have a communicable disease. Same shall report any food poisonings or prevalent illnesses to health authority by phone or telegram immediately. 1910.142(1)(1) and (2)	No specific mention

**COMPARISON
OF
PDA CH. 82
AND USDOL 29 CFR 1910.142(OSHA) AND 20 CFR 654 (ETA)
HOUSING/CAMP STANDARDS**

Note: Bolded descriptions are the strictest regulation. Where both were equal, PDA was highlighted.

<i>FIRE SAFETY</i>			
ALL buildings used as living quarters	Must comply with 34 Pa Code Chapters 49 – 59 under the Fire and panic Act or local codes. 82.17.a	General provisions of the OSHA Act	General provisions of the OSHA Act
1. Exits	Safe, adequate, reliable, accessible, unobstructed. No devices preventing egress allowed.	General provisions of the OSHA Act	General provisions of the OSHA Act Housing for >10 persons with 1 story construction with 2 means of egress. 654.417 (b) Dormitory for >10 persons, dining facilities, common rooms with 2 doors separated for fire escape. 654.417(c) Rooms on the 2 nd floor with permanent ladder or second stairway 654.417 (d)
2. Fire extinguishers	10-B minimum= Installed and maintained in each kitchen. 2-A rating=installed and maintained in each dormitory room, central/convenient to group of sleeping rooms, for each 3000 sq ft of floor area, at least one per floor.	General provisions of the OSHA Act	General provisions of the OSHA Act Fire extinguishers provided 654.417 (f)
3. Room use	Wood frame construction= 1 st and 2 nd floors occupied or used. 3 rd floor and above shall be effectively secured.	General provisions of the OSHA Act	General provisions of the OSHA Act
4. Stove pipes/fuel lines	Devises using liquid or solid fuel or electricity if closer the 36” to the wall then fireproof sheeting provided extending 6” beyond. Units tested by Am. Gas Assoc., or Underwriters Labs. Can be closer without fireproof wall if installed according to manufacturers specs. Where stovepipes pass through walls, floors, ceilings fireproof insulation shall be provided. Fuel lines located/protected to prevent breakage.	General provisions of the OSHA Act	Solid or liquid fuel stoves not used in rooms with wood or other combustible materials without proper insulation/fire proofing floor, walls, ceilings. 654.409 (b) (c) General provisions of the OSHA Act Heating pipes with fire proof materials 654.409 (c) Vents and stovepipes with metal collar 654.409 (c)

**COMPARISON
OF
PDA CH. 82
AND USDOL 29 CFR 1910.142(OSHA) AND 20 CFR 654 (ETA)
HOUSING/CAMP STANDARDS**

Note: Bolded descriptions are the strictest regulation. Where both were equal, PDA was highlighted.

Fire safety cont.			
5. Storage of materials	Petroleum gas storage vessels located outside, securely fastened, shut off valve located outside bldg, not stored under or near fire escapes or outside stairs. Flammables/volatile materials not stored in or adjacent to living rooms.	General provisions of the OSHA Act	General provisions of the OSHA Act Volatile/flammable liquids not stored in or adjacent to living units. 654.417 (h)
6. Occupancy Permit?	Single family housing units exempt. All others must have valid Permit from Pa labor and Industry. 82.17.b	General provisions of the OSHA Act	General provisions of the OSHA Act
7. Smoke detectors	1 single station smoke detector (UL) and maintained. Installed between the sleeping rooms and path of exit.	General provisions of the OSHA Act	General provisions of the OSHA Act

**COMPARISON
OF
PDA CH. 82
AND USDOL 29 CFR 1910.142(OSHA) AND 20 CFR 654 (ETA)
HOUSING/CAMP STANDARDS**

Note: Bolded descriptions are the strictest regulation. Where both were equal, PDA was highlighted.

<p><i>OCCUPANTS RESPONSIBILITY</i></p>	<p>Occupant held legally responsible concurrently with the permittee of the camp with 82.4, 82.6 (a), (b), 82.9 (k), 82.11(f), 82.13 (a), (c), (e), PROVIDED: The Department found the camp in compliance prior to occupancy of the camp and occupant has been informed of the applicable requirements in writing and in native language and has acknowledged responsibility for these requirements in writing upon a form provided by the Department. Nothing relieves owner/operator/permittee of any responsibility imposed by Ch. 82 or any other Law or Regulation. 82.18.a,b</p>	<p>No specific mention</p>	<p>No specific mention</p>
<p><i>SINGLE FAMILY HOUSING UNITS</i></p>	<p>Related as spouses, children, parents, brothers or sisters and function as one housekeeping unit. Heating, plumbing, water, sewage, and electrical systems of the other housing unit cannot affect it. SFHUs as components of a camp shall use Agreements as long as the unit is habitable (82.20 (c)) or must comply with Ch. 82 in whole. Agreements are submitted annually. 82.20. a - g</p>	<p>No specific mention</p>	<p>No specific mention</p>