

COMPARISON OF PDA CH. Ch 82, USDOL 29 CFR 29 CFR 1910.142 (OSHA) AND 20 CFR 20 CFR 654 (ETA) HOUSING/CAMP STANDARDS

| AREA OF CONCERN | PDA, Ch 82 | USDOL (OSHA) BUILT AFTER 4/80 | USDOL (ETA): BUILT BEFORE 4/80 |
|---|---|---|---|
| PERMITTING, LICENSING, APPLICATION | | | |
| | SFLC Permit Required <ul style="list-style-type: none"> - Pre-permit inspections (announced) - In-season inspections (unannounced). - Permits valid for 1 year. Renewal notices sent annually ~45 days prior to expiration. - Posting of permit in SFLC required. - Permits may be revoked or suspended at any time for violation of this chapter or the act. - Occupancy of camp may not occur without a valid permit. - New camp application must be made 60 days prior to occupancy. - Separate permits required for each camp - Plans and specifications must be submitted to the Department for any construction, remodel, alteration, or new camp. | Migrant & Seasonal Agricultural Worker Protection Act 500.130 – 500.135 defines. <ul style="list-style-type: none"> - Inspections occur randomly. - Accepts PA permit | Migrant & Seasonal Agricultural Worker Protection Act 500.130 – 500.135 defines. <ul style="list-style-type: none"> - Inspections occur randomly. - Accepts PA permit |
| OCCUPANCY | | | |
| How many? | <ul style="list-style-type: none"> - Determined by square ft of useable floor space in sleeping rooms and habitable rooms (areas where ceiling height is > 5' and > ½ of the area has a ceiling height of 7') <p><i>Ch 82.5. a and e</i></p> | <ul style="list-style-type: none"> - Determined by square ft of useable floor space in sleeping rooms and habitable rooms - 7 ft ceiling provided <p><i>29 CFR 1910.142 (b)(2)</i></p> | <ul style="list-style-type: none"> - At least ½ of the floor area in each living unit must have a minimum ceiling height of 7 ft. - No floor space may be counted toward minimum requirements where the ceiling height is < 5 ft. <p><i>20 CFR 20 CFR 654.407(g)</i></p> |
| Dorm/other sleeping quarters | <ul style="list-style-type: none"> - Shared by unrelated SFW's = 50 sq ft/adult, 25 sq ft/occupant under age 14 <p><i>Ch 82.5a(1)</i></p> | <ul style="list-style-type: none"> - >50 sq ft/person <p><i>29 FR 1910.142 (b)(2)</i></p> | <ul style="list-style-type: none"> - >50 sq ft/person for single beds - 40 sq ft /person for double bunks in dorm situations (built prior to 4/29 CFR 1980 only) <p><i>20 CFR 20 CFR 654.407 9 (c)(1) and (c)(2)</i></p> |

| AREA OF CONCERN | PDA, Ch 82 | USDOL (OSHA) BUILT AFTER 4/80 | USDOL (ETA): BUILT BEFORE 4/80 |
|---|---|--|---|
| OCCUPANCY CONT. | | | |
| Living units: 1+ rooms Where workers live, sleep and eat | <ul style="list-style-type: none"> - 100 sq ft of floor space/adult - 50 sq ft /occupant under 14 Ch 82.5a(2) | <ul style="list-style-type: none"> - >100 sq ft/person 29 CFR 1910.142 (b)(9) | <ul style="list-style-type: none"> - >60 sq ft/person 20 CFR 20 CFR 654.407 (c)(3) |
| Other requirements | <ul style="list-style-type: none"> - Family with children 6 years or older-1 rigid partition for privacy in sleeping quarters. Ch 82.5(b) | None | <ul style="list-style-type: none"> - Separate or partitioned sleeping areas for parents where children are > age 6. - Separate sleeping for each family. 20 CFR 20 CFR 654.407 (d)20 CFR 654.407 (e) |
| Sleeping Rooms contents | <ul style="list-style-type: none"> - Provided with bed, mattress & cover, pillow & cover, sheets, and blankets. (Must have linens prior to occupancy) - Single-family occupancy units, family can provide linens Ch 82.5b(a) | <ul style="list-style-type: none"> - Provided with beds, cots, bunks 29 CFR 1910.142 (b)(3) | Provided with: <ul style="list-style-type: none"> - Beds, cots, bunks - Clean mattress - Clean and sanitary linens 20 CFR 20 CFR 654.416 (a)20 CFR 654.416 (b) |
| Spacing of beds | <ul style="list-style-type: none"> - Beds, cots, bunks = 12 inches from floor/ 36'' apart all sides - Double bunks = 48''apart all sides/27'' between upper & lower - Triple bunk prohibited - Double beds = single family sleeping room only Ch 82.5b (a)(1-5) | <ul style="list-style-type: none"> - Beds, cots, bunks = >3' apart and 12'' off floor - Double bunk beds spaced >48'' both laterally and end to end - Clear space between lower and upper bunk = 27'' - Triple bunks are prohibited. - 29 CFR 1910.142 (b)(3) | No specific mention |
| Storage in sleeping rooms | <ul style="list-style-type: none"> - In the sleeping room area. - Wall or footlocker, 3 ft of rod and shelving, dresser, or equivalent/occupant. Ch 82.5b (b) | <ul style="list-style-type: none"> - Suitable storage facilities, wall lockers provided. 29 CFR 1910.142 (b)(3) | <ul style="list-style-type: none"> - Adequate facilities for hanging and storing personal effects provided. 20 CFR 20 CFR 654.401 (f) |
| Maintenance of sleeping rooms | <ul style="list-style-type: none"> - Aired, in sanitary condition at all times - Bedding and linens cleaned frequently - Single family units responsible for own frequency on cleaning Ch 82.6 (a) and (b) | No specific mention | <ul style="list-style-type: none"> - Maintained in sanitary condition 20 CFR 20 CFR 654.407(a) |

| AREA OF CONCERN | PDA, Ch 82 | USDOL (OSHA) BUILT AFTER 4/80 | USDOL (ETA): BUILT BEFORE 4/80 |
|--------------------------------------|--|---|--|
| SITE | | | |
| Drainage | Adequately drained <i>Ch 82.4</i> | Adequately drained <i>29 CFR 1910.142 (a)(1)</i> | Adequately drained <i>20 CFR 20 CFR 654.404 (a)</i> |
| Location | <ul style="list-style-type: none"> - Not within 500 ft of swamp, pools, sink holes or other surface collection of water UNLESS the water is subject to mosquito control measures. - Nor along, across or projecting into floodways or flood channel. <i>Ch 82.4 (a) and (b)</i> | <ul style="list-style-type: none"> - Shall not be subject to periodic flooding nor located within 200 ft of swamp, pools, sink holes, or other surface collections of water UNLESS the water is subject to mosquito control measures. - Drained so not to cause a danger to the domestic or public water supply. <i>29 CFR 1910.142 (a)(1)</i> | <ul style="list-style-type: none"> - Away from conditions that could create offensive odors, flies, noise, traffic, or similar hazards. - Provided with reasonable recreational space relevant to camp size <i>20 CFR 654.404 (b), 20 CFR 654.404 (d)</i> |
| Grading /exterior maintenance | <ul style="list-style-type: none"> - Site graded, ditched, or rendered free from depressions <i>Ch 82.4(a)</i> | <ul style="list-style-type: none"> - Site graded, ditched, or rendered free from depressions <i>29 CFR 1910.142 (a)(1)</i> | <ul style="list-style-type: none"> - Free from debris, poisonous plants, uncontrolled weeds, or brush <i>20 CFR 654.404(c)</i> |
| Location near farm animals | <ul style="list-style-type: none"> - At least 50 ft from area with livestock (with some exceptions) - Animal waste produced for ag. purposes must 500 ft away and be managed to not be a nuisance or fly breeding medium <i>Ch 82.4. c and f</i> | <ul style="list-style-type: none"> - <i>At least 500 ft from area where livestock are kept.</i> <i>29 CFR 1910.142(a)(2)</i> | No comments regarding |
| Grounds | <ul style="list-style-type: none"> - Clean and sanitary, free from refuse, debris, wastepaper, garbage, noxious plants, uncontrolled weeds, abandoned autos, or other refuse. - Removal of all refuse when camp is closed and privy locked. <i>Ch 82.4(d)</i> | <ul style="list-style-type: none"> - Clean and sanitary, free from rubbish, debris, wastepaper, garbage, or other refuse. - Removal of all refuse when camp is closed and privy locked. <i>29 CFR 1910.142(a)(3)</i> | <ul style="list-style-type: none"> - Free from debris, poisonous plants, uncontrolled weeds, or brush <i>20 CFR 654.404(c)</i> |

| AREA OF CONCERN | PDA, Ch 82 | USDOL (OSHA) BUILT AFTER 4/80 | USDOL (ETA): BUILT BEFORE 4/80 |
|---|---|---|---|
| HOUSING/SHELTER | | | |
| Construction/repair: Windows | In habitable rooms <ul style="list-style-type: none"> - Weather tight, operable, in good repair and: - size = 10% of floor area - 45% of window area openable (unless otherwise ventilated). - Fitted screens with 16" mesh during insect season Ch 82.5(f) | In all living quarters <ul style="list-style-type: none"> - total window area >1/10th of floor area. - ½ of window openable for ventilation. - Screened with 16" mesh at all times. - In good repair 29 CFR 1910.142 (b)(7), (8), and (1) | In all living quarters <ul style="list-style-type: none"> - total window area >1/10th of floor area. - Total openable window space > 45% of the minimum window area required, except where adequate ventilation is provided. - Screened with 16" mesh. 20 CFR 654.408(a), 54.407 (h) |
| Heat | <ul style="list-style-type: none"> - Space heating equipment: safely and adequately heating all habitable rooms to 68°F from September 15 thru May 15. - Unvented or unable to be vented heaters with a flame are prohibited. Ch 82.5(h) and (i) | <ul style="list-style-type: none"> - Adequate heating equipment provided if camp is used during the cold weather. - Equipment installed via state and local Laws. 29 CFR 1910.142(b)(11) | <ul style="list-style-type: none"> - Provided if temp falls below 68°F - Installed properly and in good repair so temp is maintained at 68°F or above. - Heat sources with combustible fuel vented. - No portable heater other than electric. 20 CFR 654.409 (a) 20 CFR 654.409 (b) |
| WATER | | | |
| Availability and supplied | <ul style="list-style-type: none"> - Shall be provided with an approved water supply. Ch 82.7(a) | <ul style="list-style-type: none"> - Shall be distributed so that no shelter is more than 100 feet from a yard hydrant if water is not piped to the shelter. - Shall have water provided for drinking, cooking, bathing, and laundry purposes. - Adequate heating equipment provided during cold months. 29 CFR 1910.142(f)(3) & 1910.142 (c)(1) | <ul style="list-style-type: none"> - Adequate and convenient water supply provided. 20 CFR 654.405 (a) |
| Heating equipment | <ul style="list-style-type: none"> - Supplied and maintained. - Unvented or unable to be vented heaters with a flame are prohibited. Ch 82.5 (i) | <ul style="list-style-type: none"> - Installed and operated according to State and Local Codes. 29 CFR 1910.142 (b)(11) | <ul style="list-style-type: none"> - Heating pipes of fireproof materials. - Vents with metal collars. 20 CFR 654.409(c) |

| AREA OF CONCERN | PDA, Ch 82 | USDOL (OSHA) BUILT AFTER 4/80 | USDOL (ETA): BUILT BEFORE 4/80 |
|---------------------------|---|--|--|
| WATER | | | |
| Hot water supplied | <ul style="list-style-type: none"> - Hot water (120°f) shall be provided to kitchens, lavatories, showers, tubs, and laundry. - Hot and cold water supplied to the kitchen and laundry facilities. <p>Ch 82.7.i and Ch 82.11.d</p> | <ul style="list-style-type: none"> - Adequate supply of hot and cold water available for drinking, cooking, bathing, and laundry purposes. <p>29 CFR 1910.142(b)(11)</p> | <ul style="list-style-type: none"> - Sinks with hot and cold water provided. <p>20 CFR 654.413(b)(5)</p> |
| Supply approved | <ul style="list-style-type: none"> - Approved water system (Pa Safe Drinking Water Act). - Non-public water systems testing for total Coliform and nitrates/nitrites annually and supplied at the initial inspection and passed. - Unapproved systems made inaccessible to camp residents. <p>Ch 82.7. (a-f)</p> | <ul style="list-style-type: none"> - Approved by the appropriate Health authority. <p>29 CFR 1910.142 (c)(1)</p> | <ul style="list-style-type: none"> - Must meet State Health Department Standards. <p>20 CFR 654.405 (a)</p> |
| Supply demands | <ul style="list-style-type: none"> - Delivers 50 gal/person/day at peak time at a peak rate of 2 ½ times the average hourly demand and capable of providing a maximum daily and hourly demands. <p>Ch 82.7(g)</p> | <ul style="list-style-type: none"> - Adequate if delivers 35 gal/person/day at peak rate of 2 ½ x the average hourly demand. <p>29 CFR 1910.142 (c)(1) and (2)</p> | <ul style="list-style-type: none"> - Adequate water supply - Must meet State Health Authority Standards <p>20 CFR 654.405(a)</p> |
| Supply pressure | <ul style="list-style-type: none"> - Normal operating pressure (fixtures not less than 8lbs/sq ft and direct flush valves not less than 15 lbs./sq ft) supplied to all fixtures for simultaneous operation. <p>Ch 82.7(h)</p> | <ul style="list-style-type: none"> - Normal operating pressure (fixtures not less than 8lbs/sq ft and direct flush valves not less than 15 lbs./sq ft) supplied to all fixtures for simultaneous operation. <p>29 CFR 1910.142(c)(3)</p> | <ul style="list-style-type: none"> - Water under pressure for bathing and hand washing. <p>20 CFR 654.412 (a)</p> |
| Drinking fountains | <ul style="list-style-type: none"> - 1 or more /100 occupants or a fraction thereof (excluded SFHU). - Impervious materials. - Angle jet nozzle with non-oxidizing guard above the rim of the bowl. Pressure regulating valve. Kept sanitary. - If inadequate, single service cup must be provided (waste receptacle). <p>Ch 82.7(j)</p> | <ul style="list-style-type: none"> - Where water is available under pressure, 1+ fountains shall be provided/100 occupants or a fraction thereof. - Construction must meet ANSI Standard Specifications (Z4.2-29 CFR 1942). - Common drinking cups prohibited. <p>29 CFR 1910.142 (c)(4)</p> | <p>Not applicable</p> |

| AREA OF CONCERN | PDA, Ch 82 | USDOL (OSHA) BUILT AFTER 4/80 | USDOL (ETA): BUILT BEFORE 4/80 |
|-----------------------------|--|---|---|
| PLUMBING | | | |
| Installed/maintained | <ul style="list-style-type: none"> - To safely carry adequate quantities of water to required locations and properly convey sewage and liquid wastes from the location to the sewage disposal system. - In accordance with 29 CFR 1978 edition of Basic Plumbing Code (BOCA) or any edition in effect at time of construction. - Prevent contamination of water supply. - Prevent unsanitary conditions or nuisance. <p>Ch 82.8(a) & (b)</p> | <ul style="list-style-type: none"> - General Provisions of OSHA | <ul style="list-style-type: none"> - Maintained to allow for disposal of sewage. <p>20 CFR 654.406 (a)</p> |
| TOILET FACILITIES | | | |
| Numbers | <ul style="list-style-type: none"> - Adequate for the capacity of the camp. - Separate for sexes. - 1 –5 occupants of 1 sex = 1 - 6 – 30 occupants of 1 sex = 2 - 31– 45 occupants of 1 sex= 3 - 46 – 60 occupants of 1 sex= 4 - If <6 occupants irrespective of sex = 1, if locked from the inside and in a single occupancy toilet facility. - SFHU's and apartments = each with its own. <p>Ch 82.9.a,b,e</p> | <ul style="list-style-type: none"> - Adequate for the capacity of the camp. - Separate for sexes in multifamily/barracks type units. - 1 unit/ 15 persons. With a minimum of 2 units for any shared facility. <p>29 CFR 1910.142 (d)(3) and (5)</p> | <ul style="list-style-type: none"> - 1 unit/15 occupants. - Separate for sexes. <p>20 CFR 654.411(b)</p> |
| Urinals | <ul style="list-style-type: none"> - 2 linear ft of trough or 1-unit/18 men. - # of water closets needed reduced by 1/3 by installing urinals. <p>Ch 82.9(c)</p> | <ul style="list-style-type: none"> - 2 linear ft or 1 unit/ 25 men. - Adequate water flush, drain freely and exclude pests. <p>29 CFR 1910.142 (d)(6)</p> | <ul style="list-style-type: none"> - Non-absorbent material. - Substituted in a ratio of 1 urinal or 24" for one toilet up to 1/3. <p>20 CFR 654.411(c)</p> |
| Structure | <ul style="list-style-type: none"> - In central toilets, water closets separated by partitions. - If facilities for each sex are in the same building, then separate by solid walls or partitions extending from floor to ceiling/roof. - Floor around urinals (>15" from outer edge) = impervious materials. - Sanitary design/cleanable. | <ul style="list-style-type: none"> - If facilities for each sex are in the same building, then separate by solid walls or partitions extending from floor to ceiling/roof. - Floor around urinals (>15" from outer edge) = impervious materials. - Windows not less than 6 sq ft in | <ul style="list-style-type: none"> - Men & women facilities separated by solid walls floor to ceiling. - Fly tight structure - Well lighted, ventilated, sanitary - Constructed to prevent nuisance/health hazard |

| | | | |
|-------------------------------|--|--|---|
| <p>Structure cont.</p> | <ul style="list-style-type: none"> - A window not less than 6 sq ft in area opening directly to the outside or satisfactorily ventilated (properly screened). - Privy building vented by opening at least 2 sq ft. - Outside openings screened with 16” mesh. - 20-foot candles of light at any time. - Approaches to may not be obstructed. <p>Ch 82.9 (a)(c)(d)(e)(g)(i)</p> | <p>areas opening directly to the outside or otherwise vented.</p> <ul style="list-style-type: none"> - Outside openings screened with 16” mesh. - Lighted naturally or artificially by safe lighting all times. <p>29 CFR 1910.142(d)(4), 29 CFR 1910.142(d)(2), 29 CFR 1910.142 (d)(8)</p> | <p>20 CFR 654 411 (a)(d)(f)(h)</p> |
| <p>Located</p> | <ul style="list-style-type: none"> - No fixture, water closet, urinal, chemical toilet shall be located in a room other than for toilet purposes. - Nor within 200 ft of sleeping room door. - Not closer than 100 ft to a sleeping room, dining room, lunch, or kitchen room. <p>Ch 82.9.(f)(h)</p> | <ul style="list-style-type: none"> - So as to be accessible without any individual passing through any sleeping room. - Pits/vaults keep out rodents and flies. - Installed after 8/31/71: located in toilet room. - Within 200 ft of sleeping room door. - Not closer than 100 ft to a sleeping room, dining room, lunch, or kitchen room. <p>29 CFR 1910.142(c)(4),29 CFR 1910.142(d)(3), 29 CFR 1910.142 (d)(6), 29 CFR 1910.142(d)(7)</p> | <ul style="list-style-type: none"> - <200’ from living units - >50’ from living/cooking areas - Located to prevent nuisance/health hazard. <p>20 CFR 654.411 (a)(g)(h)</p> |
| <p>Supplied</p> | <ul style="list-style-type: none"> - Adequate supply of toilet paper in each privy, water closet or chemical toilet compartment. - Kept in clean and sanitary condition. - Must be signed in English and native language of occupant or marked with understandable picture or symbol. <p>Ch 82.9.j and k</p> | <ul style="list-style-type: none"> - Adequate supply of toilet paper in each. - Kept sanitary and cleaned daily <p>29 CFR 1910.142(d)(9)(10)</p> | <ul style="list-style-type: none"> - Toilet tissue supplied (common use facilities) - Marked “men” & “women” in native language <p>20 CFR 654.411 (d)(e)</p> |

| AREA OF CONCERN | PDA, Ch 82 | USDOL (OSHA) BUILT AFTER 4/80 | USDOL (ETA): BUILT BEFORE 4/80 |
|--------------------------------------|--|--|--|
| LAUNDRY/HAND WASHING/ BATHING | | | |
| Numbers | <ul style="list-style-type: none"> - 1 hand wash basin/6 persons - 1 showerhead/10 persons - 1 mechanical washing machine or double laundry tray or 2 tubs /30 persons - OR transportation 1x weekly - OR commercial linen service - 1 slop sink/camp - 1 tub/6 occupants as an alternative to showers. <p>Ch 82.11.a</p> | <ul style="list-style-type: none"> - 1 hand wash basin/family - or 6/persons in shared facility - 1 showerhead/10 persons - 1 laundry tub or tray/ 30 persons - 1 slop sink/building <p>29 CFR 1910.142 (f)(2) (i),(ii),(iii),(iv)</p> | <ul style="list-style-type: none"> - Showerheads = 1/15 - Wash basins = 1/15 - Laundry tub/trays = 1/25 - OR Washing machine = 1/50 - Separate shower facilities for sexes (except family units) <p>20 CFR 654.412 (b) (c) (d)</p> |
| Floors | <ul style="list-style-type: none"> - Non-slippery finish, easily cleanable surface, impervious to moisture, floor drains provided, floor/wall coving installed. Shower room walls/floor smooth and impervious to height of splash. <p>Ch 82.11.(b)(c)</p> | <ul style="list-style-type: none"> - Smooth finish, not slippery, impervious to moisture, drains provided, curbing and floors coved, walls/shower partitions smooth and impervious to height of splash. <p>29 CFR 1910.142 (f)(2)</p> | <ul style="list-style-type: none"> - Nonabsorbent, nonskid, with proper drains. <p>20 CFR 654.412 (b)</p> |
| Other | <ul style="list-style-type: none"> - Adequate hot and cold running water with normal operating pressure. - Facilities to dry clothing provided. - Bathing tubs—adequate hot and cold water under pressure. - Common towels prohibited. - Dry dressing area provided in or adjacent to shower facility. <p>Ch 82.11(d)(e)(f)(g)(i)(j)</p> | <ul style="list-style-type: none"> - Adequate hot and cold running water provided. - Facilities for heating water provided. - Service buildings provided with heat (70°f) - Facilities for drying clothing provided. - Kept clean. <p>29 CFR 1910.142 (f)(3)(4)(5)(6)</p> | <ul style="list-style-type: none"> - Bathing and hand washing provided, hot and cold water under pressure provided in bathing, laundry and hand washing areas, maintained clean and sanitary, located within 200' of living unit. - Shower area with >9sq ft of floor space/worker. <p>20 CFR 654.412(a)(b)</p> |

| AREA OF CONCERN | PDA, Ch 82 | USDOL (OSHA) BUILT AFTER 4/80 | USDOL (ETA): BUILT BEFORE 4/80 | | | | | | | | | | | | |
|--|---|---|--|--|------------|---|----|-------------------------------------|------------------------|-----------------|------------------------|--|--|---|--|
| SEWAGE | | | | | | | | | | | | | | | |
| | <ul style="list-style-type: none"> - Approved by the Department or the municipal Sewage Enforcement Officer <p>(Ch 71,73, and 243 and The Clean Streams Act). Ch 82.10</p> | <ul style="list-style-type: none"> - In camps where public sewers are available, all sewer lines and floor drains from the buildings shall be connected thereto. <p>29 CFR 1910.142 (e)</p> | <ul style="list-style-type: none"> - Facilities for effective disposal provided, maintained, connection to public sewer where available. - Portable privies provided where public sewer or septic not available. <p>20 CFR 654.406 (a)(b)(c)</p> | | | | | | | | | | | | |
| LIGHTING/ELECTRICAL | | | | | | | | | | | | | | | |
| Installed/maintained | <ul style="list-style-type: none"> - Must comply with UCC, except for those built prior to 1/3/81; which comply with code in effect at time of construction. Proof of building code inspection. | <ul style="list-style-type: none"> - General provisions of OSHA, BOCA, NEC, state, and local codes | <ul style="list-style-type: none"> - Electricity provided. - Wiring and lighting fixtures in safe condition. - General provisions of OSHA, BOCA, NEC, State, and local codes. <p>20 CFR 654.410 (a)(d)</p> | | | | | | | | | | | | |
| Levels (Measured minimum 30" from the floor) | <table border="1" style="width: 100%;"> <thead> <tr> <th style="text-align: left;">Area</th> <th style="text-align: left;">Foot candles</th> </tr> </thead> <tbody> <tr> <td>Halls/stairways storage Dining Rm (for cleaning)</td> <td>Food 10</td> </tr> <tr> <td>Living quarters Private sleeping Dorm sleeping Toilet/bathing: Shared and private Chemical toilets Laundry Rm Habitable rooms</td> <td>20</td> </tr> <tr> <td>Communal kitchen Private kitchen</td> <td>30 (work)/20 (general)</td> </tr> <tr> <td>Central kitchen</td> <td>35 (work)/20 (general)</td> </tr> <tr> <td colspan="2">One ceiling or lighting type fixture is required in laundry room, halls/stairways, habitable rms/living quarters, toilet /bathing rms (private or shared).</td> </tr> </tbody> </table> | Area | Foot candles | Halls/stairways storage Dining Rm (for cleaning) | Food 10 | Living quarters Private sleeping Dorm sleeping Toilet/bathing: Shared and private Chemical toilets Laundry Rm Habitable rooms | 20 | Communal kitchen Private kitchen | 30 (work)/20 (general) | Central kitchen | 35 (work)/20 (general) | One ceiling or lighting type fixture is required in laundry room, halls/stairways, habitable rms/living quarters, toilet /bathing rms (private or shared). | | <ul style="list-style-type: none"> - Light levels in toilet and storage areas = 20 foot candles measured 30" from floor. - Other rooms = 30-foot candles 30" from the floor - Where service is available: - Habitable Room = 1 ceiling type light fixture - Laundry room, toilet room, rooms where people congregate = 1 ceiling or wall-type fixture. | <ul style="list-style-type: none"> - Adequate ceiling/wall type fixtures in all rooms. - Adequate lighting for pathways and yard. <p>20 CFR 654.410 (b)(c)</p> |
| | Area | Foot candles | | | | | | | | | | | | | |
| | Halls/stairways storage Dining Rm (for cleaning) | Food 10 | | | | | | | | | | | | | |
| | Living quarters Private sleeping Dorm sleeping Toilet/bathing: Shared and private Chemical toilets Laundry Rm Habitable rooms | 20 | | | | | | | | | | | | | |
| | Communal kitchen Private kitchen | 30 (work)/20 (general) | | | | | | | | | | | | | |
| | Central kitchen | 35 (work)/20 (general) | | | | | | | | | | | | | |
| | One ceiling or lighting type fixture is required in laundry room, halls/stairways, habitable rms/living quarters, toilet /bathing rms (private or shared). | | | | | | | | | | | | | | |
| Ch 82.12(c) | 29 CFR 1910.142 (g) | | | | | | | | | | | | | | |

| AREA OF CONCERN | | PDA, Ch 82 | USDOL (OSHA) BUILT AFTER 4/80 | USDOL (ETA): BUILT BEFORE 4/80 |
|----------------------------|---|---|--|---|
| LIGHTING/ELECTRICAL | | | | |
| Outlets | Room | Outlet number | 1 separate floor or wall-type convenience outlet in each habitable room. 29 CFR 1910.142 (g) | Electrical outlets provided in each room. 20 CFR 654.410 (b) |
| | Food storage Halls/stairways | 0 | | |
| | Laundry Habitable rms/living quarters Toilet/bathing private Toilet shared Sleeping private Sleeping, Dorm | 1 1/2 sinks 1/person 1/5 people | | |
| | Existing central, communal, private kitchens New kitchen | 2 (1 = 20 amp) 2, 20 amp | | |
| | Not permitted on floor surface Ch 82.12(d) | | | |
| REFUSE | | | | |
| Type | <ul style="list-style-type: none"> - Those containing food waste: leak proof, nonabsorbent, rust/corrosion resistant, tight-fitting lids, kept clean. - Other refuse: sufficient size; must prevent arthropod/rodent/other nuisances. Ch 82.13.(a)(b) | <ul style="list-style-type: none"> - Fly-tight, rodent-tight, impervious, cleanable, or single service containers, approved by the local health authority, kept clean. 29 CFR 1910.142 (h) (1) and (2) | <ul style="list-style-type: none"> - Fly tight 20-gallon container provided adjacent to housing unit = 1/15persons 20 CFR 654.414 (a) | |
| Located | <ul style="list-style-type: none"> - Adjacent and convenient to kitchens, dining rooms, living quarters and toilet rooms. Ch 82.139(c) | <ul style="list-style-type: none"> - Within 100 ft of each shelter and on wood, metal, or concrete stand. 29 CFR 1910.142 (h)(1) | <ul style="list-style-type: none"> - Fly tight 20-gallon container provided adjacent to housing unit = 1/15persons 20 CFR 654.414 (a) | |
| Numbers | <ul style="list-style-type: none"> - Sufficient in number. Ch 82.13.b | <ul style="list-style-type: none"> - 1/family shelter 29 CFR 1910.142 (h)(1) | <ul style="list-style-type: none"> - 1/15 persons 20 CFR 654.414 (a) | |
| Disposal | <ul style="list-style-type: none"> - 1x/week emptied or whenever full. - Containers kept clean after removal. - Shall conform to the July 7, 29 CFR 1980 Solid Waste Management Act and 25 Pa. Code Part I, Subpart D, Article VIII. Ch 82.13.(d)(e)(f) | <ul style="list-style-type: none"> - Emptied when full but not less the 2x/week. 29 CFR 1910.142 (h)(3) | <ul style="list-style-type: none"> - Collected 2 x /week or more often. 20 CFR 654.414 (b) | |

| AREA OF CONCERN | PDA, Ch 82 | USDOL (OSHA) BUILT AFTER 4/80 | USDOL (ETA): BUILT BEFORE 4/80 |
|---|---|---|---|
| RODENT/INSECT CONTROL | | | |
| Prevention | <ul style="list-style-type: none"> - Effective control measures and environmental changes approved by the Dept. to control infestations and harborage of animals and insects. <p>Ch 82.15.(a)</p> | <ul style="list-style-type: none"> - Effective measures shall be taken to prevent infestation by and harborage of animal or insect vectors or pests. <p>29 CFR 1910.142(j)</p> | <ul style="list-style-type: none"> - Free from rodent, insect, vermin <p>20 CFR 654.415</p> |
| Other | <ul style="list-style-type: none"> - Agricultural pesticides and toxic chemicals may not be stored in housing areas. <p>Ch 82.15.(c)</p> | <ul style="list-style-type: none"> - Poisonous/toxic materials not stored with food or in food prep areas. <p>29 CFR 1910.142 (i)</p> | <ul style="list-style-type: none"> - Pesticides and other chemicals not stored in housing unit. <p>20 CFR 654.417(i)</p> |
| FOOD SERVICE/KITCHENS | | | |
| Location | <ul style="list-style-type: none"> - Private Kitchens: space separated but not necessarily partitioned. - Communal Kitchens: in a room or building separate from the sleeping areas. <p>Ch 82.14.(a)(b)</p> | <ul style="list-style-type: none"> - Separate from the sleeping quarters of any workers or their families. - No direct opening from living or sleeping quarters into kitchen or dining halls. <p>29 CFR 1910.142 (i)(2)</p> | <ul style="list-style-type: none"> - In family units cooking and eating equipment provided. - Central mess kitchens separate from sleeping quarters. <p>20 CFR 654.413 (a)(d)</p> |
| Supplied Private and communal kitchens | <ul style="list-style-type: none"> - Stove/hot plate with minimum of 2 burners (2 burners/10 persons or 2 families) - Food storage shelves - Counter for food prep - Mechanical refrigeration to maintain 45°f or below and freezer accommodations. - Table and chairs adequate for capacity of camp - Adequate sinks with hot/cold running water under normal pressure - Lighting and ventilation <p>Ch 82.14(a)(b)</p> | <ul style="list-style-type: none"> - Employer must provide each worker 3 meals a day or furnish free and convenient cooking/kitchen facilities so workers can prepare their own meals. - Where the employer provides the meals, the job offer will state the charge, if any, to the worker for such meals. Amount of meal § 655.173 - Appliances must be sufficient to allow workers to safely prepare 3 meals per day, cannot only be an electric hot plate, microwave, or outdoor community grill. Rental and public accommodations that do not provide kitchen facilities - employers must provide 3 meals per day. <p>20 CFR 655.122(g)</p> | <ul style="list-style-type: none"> - Family units/common facilities for families: cook stove with min of 2 burners (1 stove/10 people) - Shelves and counter space - Mechanical refrigeration (<45 f); tables and chairs provided to accommodate capacity - Provided with adequate light and ventilation. - In common facilities, sinks with hot and cold water under pressure. <p>20 CFR 654.413 (a) (b)(b,5)</p> |

| AREA OF CONCERN | PDA, Ch 82 | USDOL (OSHA) BUILT AFTER 4/80 | USDOL (ETA): BUILT BEFORE 4/80 |
|--|--|---|--|
| FOOD SERVICE/KITCHENS | | | |
| Sanitation in food service kitchens | <ul style="list-style-type: none"> - Physical facilities, equipment and operation shall comply with Ch. 78, relating to food establishments, in central kitchens. <p>Ch 82.14.(c)(d)</p> | <ul style="list-style-type: none"> - In all camps where dining or multiple family feeding operations are permitted or provided, the food handling facility shall comply with the requirement of the "Food Service Sanitation Ordinance and Code," Part V of the "Food Service Sanitation Manual," U.S. public health Service Publication 934 (29 CFR 1965). - No person with any communicable disease shall be employed or permitted to work in the preparation, cooking, serving, or handling of food, foodstuffs, or materials used therein, in any dining room or kitchen used by persons living in a camp. - Free from vermin, flies, rodents. - No spoiled food. Equipment and utensils clean. - Kitchen clean. <p>29 CFR 1910.142(i)(1)(3)</p> | <ul style="list-style-type: none"> - Walls of nonabsorbent, cleanable materials. <p>20 CFR 654.413 (d)</p> |
| Fire safety in kitchens | <ul style="list-style-type: none"> - Wall surfaces adjacent to cooking areas shall be fire-resistant. <p>Ch 82.14(d)</p> | <ul style="list-style-type: none"> - General provisions of OSHA | <ul style="list-style-type: none"> - General provisions of OSHA, state, and local fire codes - Wall surfaces adjacent to cooking areas = fire resistant materials. <p>20 CFR 654.417 (a), 20 CFR 654.413 (d)</p> |
| FIRST AID | | | |
| How many? | <ul style="list-style-type: none"> - 1 kit/50 persons or fraction thereof. <p>Ch 82.16(a)</p> | <ul style="list-style-type: none"> - Adequate first aid facilities approved by a health authority shall be maintained and made available in every camp. <p>29 CFR 1910.142(k)(1)</p> | <ul style="list-style-type: none"> - Provided <p>20 CFR 654.417 (g)</p> |

| AREA OF CONCERN | PDA, Ch 82 | USDOL (OSHA) BUILT AFTER 4/80 | USDOL (ETA): BUILT BEFORE 4/80 |
|--|--|--|--|
| FIRST AID | | | |
| Contents | <p>Shall include:</p> <ul style="list-style-type: none"> - 50 adhesive compress, 10 4x4 gauze pads, 20 3x3 gauze pads, 10 2x2 gauze pads, 2 gauze roller bandage, 1 roll adhesive tape (1" and ½"), 50 cotton balls, 50 cotton swabs, 12 aromatic ammonia inhalants, 1 8oz ethyl or isopropyl alcohol, 1 8oz benzalkonium chloride, 1 scissors, 1 tweezers. <p>Ch 82.16(a)</p> | No specific mention | No specific mention |
| Responsibility | <ul style="list-style-type: none"> - 1 designated person trained to administer first aid shall be in charge of the kit and be accessible at all times. <p>Ch 82.16(b)</p> | <ul style="list-style-type: none"> - 1 person trained to administer first aid and shall be in charge of kit and readily accessible at all times. <p>29 CFR 1910.142 (k)(2)</p> | No specific mention |
| COMMUNICABLE DISEASE REPORTING | See Ch. 78 for communal kitchens operations | <ul style="list-style-type: none"> - Camp superintendent shall report to the Health Authority if camp individual is known to have a communicable disease. - Same shall report any food poisonings or prevalent illnesses to health authority by phone or telegram immediately. <p>29 CFR 1910.142(l) (2)</p> | No specific mention |
| FIRE SAFETY | | | |
| ALL buildings used as living quarters | <ul style="list-style-type: none"> - Must comply with the Uniform Construction Code | General provisions of the OSHA Act | General provisions of the OSHA Act |
| Exits | <ul style="list-style-type: none"> - Safe, adequate, reliable, accessible, unobstructed. - No devices preventing egress allowed. | General provisions of the OSHA Act | General provisions of the OSHA Act. <ul style="list-style-type: none"> - Housing for >10 persons with 1 story construction with 2 means of egress. - Dormitory for >10 persons, dining facilities, common rooms with 2 doors separated for fire escape. - Rooms on the 2nd floor with permanent ladder or second stairway 20 CFR 654.417 (b)(c)(d) |

| AREA OF CONCERN | PDA, Ch 82 | USDOL (OSHA) BUILT AFTER 4/80 | USDOL (ETA): BUILT BEFORE 4/80 |
|-------------------------------|---|------------------------------------|--|
| FIRE SAFETY | | | |
| Fire extinguishers | <ul style="list-style-type: none"> - 10-B minimum= Installed and maintained in each kitchen. - 2-A rating=installed and maintained in each dormitory room, central/convenient to group of sleeping rooms, for each 3000 sq ft of floor area, at least one per floor. <p>Ch 82.17(a)(2)(3)</p> | General provisions of the OSHA Act | <ul style="list-style-type: none"> - General provisions of the OSHA Act - Fire extinguishers provided within 100 ft of each housing unit. - Fire extinguishing equipment must provide protection equal to 2 1/2/ gallon stored pressure or 5-gallon pump-type water extinguisher. <p>20 CFR 654.417 (f)</p> |
| Room use | <ul style="list-style-type: none"> - Wood frame construction= 1st and 2nd floors occupied or used. - 3rd floor and above shall be effectively secured. <p>Ch 82.14</p> | General provisions of the OSHA Act | General provisions of the OSHA Act |
| Stove pipes/fuel lines | <ul style="list-style-type: none"> - Devices using liquid or solid fuel or electricity if closer the 36" to the wall then fireproof sheeting provided extending 6" beyond. Units tested by Am. Gas Assoc., or Underwriters Labs. Can be closer without fireproof wall if installed according to manufacturers specs. Where stovepipes pass through walls, floors, ceilings fireproof insulation shall be provided. Fuel lines located/protected to prevent breakage. | General provisions of the OSHA Act | <p>General provisions of the OSHA Act</p> <ul style="list-style-type: none"> - Solid or liquid fuel stoves not used in rooms with wood or other combustible materials without proper insulation/fire proofing floor, walls, ceilings. - Heating pipes with fireproof materials. - Vents/stovepipes with metal collar. <p>20 CFR 654.409 (b) (c)</p> |
| Storage of materials | <ul style="list-style-type: none"> - Petroleum gas storage vessels located outside, securely fastened, shut off valve located outside bldg, not stored under or near fire escapes or outside stairs. - Flammables/volatile materials not stored in or adjacent to living rooms. | General provisions of the OSHA Act | <p>General provisions of the OSHA Act</p> <ul style="list-style-type: none"> - Volatile/flammable liquids not stored in or adjacent to living units. <p>20 CFR 654.417 (h)</p> |
| Occupancy Permit | <ul style="list-style-type: none"> - Single family housing units exempt. - All others must have an occupancy permit issued by local municipality as applicable. | General provisions of the OSHA Act | General provisions of the OSHA Act |
| Smoke detectors | <ul style="list-style-type: none"> - 1 single station smoke detector (UL) and maintained. Installed between the sleeping rooms and path of exit. | General provisions of the OSHA Act | General provisions of the OSHA Act |

| AREA OF CONCERN | PDA, Ch 82 | USDOL (OSHA) BUILT AFTER 4/80 | USDOL (ETA): BUILT BEFORE 4/80 |
|------------------------------------|---|-------------------------------|--------------------------------|
| OCCUPANTS RESPONSIBILITY | <ul style="list-style-type: none"> - Occupant held legally responsible concurrently with the permittee of the camp with Ch 82.4, Ch 82.6 (a), (b), Ch 82.9 (k), Ch 82.11(f), Ch 82.13 (a), (c), (e), - PROVIDED: The Department found the camp in compliance prior to occupancy of the camp and occupant has been informed of the applicable requirements in writing and in native language and has acknowledged responsibility for these requirements in writing upon a form provided by the Department. - Nothing relieves owner/operator/permittee of any responsibility imposed by Ch. Ch 82 or any other Law or Regulation. <p>Ch 82.18.(a)(b)</p> | No specific mention | No specific mention |
| SINGLE FAMILY HOUSING UNITS | <ul style="list-style-type: none"> - Related as spouses, children, parents, brothers or sisters and function as one housekeeping unit. - Heating, plumbing, water, sewage, and electrical systems of the other housing unit cannot affect it. - SFHUs as components of a camp shall use Agreements as long as the unit is habitable (Ch 82.20 (c)) or must comply with Ch. Ch 82 in whole. - Agreements are submitted annually (Ch 82.20. a – g) | No specific mention | No specific mention |

Note: Bolded descriptions are the strictest regulation. Where both were equal, PDA was highlighted.