	Temporary License	Permanent License
HANDWASH SINKS		
Where to wash	Convenient, accessible and	Convenient, accessible and
Watan Carpha***	with overhead protection	with overhead protection
Water Supply***	Must be an approved	Must be an approved
	source	source
Water connections and/or	May be direct connection	May be direct connection
holding containers***	to a provided flowing	to a provided flowing
	water supply or may be an	water supply or may be an
	approved water holding	approved water holding
	container, tank, or other	container, tank or other
	approved holding unit.	approved holding unit.
Connection to sink***	If a portable container, may	If a portable container, may
	be placed above the basin	gravity drop into the sink.
	and may simply gravity	Buckets may not be used.
	drop into basin/bucket. If	If direct connected to a
	direct connected to a	constant water supply at an
	constant water supply,	event, must be connected
	must be attached so no	so no contamination occurs
	contamination occurs to the	to the water supply.
	water supply.	
Faucets***	Water must flow freely,	Water must flow freely,
	therefore dispensing spouts	therefore dispensing spouts
	are required. No push	are required. No push
	buttons.	buttons.
Water temperature	Must be 80F or above. Hot	Must be 80F or above. Hot
	water may be used to fill	water must be plumbed to
	the potable water supply.	the sinks or otherwise
		supplied to the water
		holding tanks.
Type of Sink/Basin	Sinks or basins/buckets	No basins or buckets.
	may be used	Proper sinks must be
		supplied.
Drain***	No drain from the basin is	A drain must be supplied &
	required	plumbed from the sink to
		an approved waste
		container/ retention tank.
Plumbing***	Plumbing is not required	Plumbing is required from
	from water holding	water holding tank (if not
	containers to the	gravity fed) to sink and
	basin/bucket and to waste	from the sink to the waste
	container	container
Connection to waste***	Waste water collected in	Waste shall be conveyed to
	the basins or buckets must	the container/retention tank

Events with Temporary Licenses VS. Permanent Licenses Handwashing and Warewashing Stations

	be emptied regularly and placed directly into the sanitary sewer or a waste retention container. Waste water collected in an approved waste retention container must be disposed of in an approved sanitary sewer	via approved plumbing. Retention tanks must be emptied as necessary into an approved sanitary sewer system.
Waste Container & Retention Tanks***	Shall have a tight fitting, vented lid. Any waste retention tanks/collection buckets shall be 15% greater then the water supply for those facilities with fixed water holding tanks. For those facilities directly connected to the water supply, the waste containers must be closely monitored and disposed of into an approved waste water disposal area as necessary.	Shall be connected to the sink via approved plumbing. Any waste retention tanks shall be 15% greater then the water supply for those facilities with fixed water holding tanks. For those facilities directly connected to the water supply, the waste containers must be closely monitored and disposed of into an approved waste water disposal area as necessary.
Direct Connections to the	Tight fitting plumbing and	Tight fitting plumbing and
Sanitary Sewer***	hoses. Connected in a manner not to contaminate the grounds or other potable water systems	hoses. Connected in a manner not to contaminate the grounds or other potable water systems
Other	Signage, soap, paper towels, waste receptacle	Signage, soap, paper towels, waste receptacle
WAREWASHING SINKS		
*** SAME AS ABOVE		
for most items. Types of sinks/basins	Basins and/or buckets with	No bucket/basins. Must be
	free flowing water supply is approved. 3- comp method (or 2 if approved)	a proper 3-comp sink (or 2- comp if approved).
Water Temperature	110F	110F
Process	Must wash, rinse, sanitize and air dry	Must wash, rinse, sanitize and air dry
Where to wash	Protected area with overhead protection. Nearby depot is allowed but must be inspected	Protected area with overhead protection. Nearby depot is allowed but must be inspected

07/30/10